

(19) World Intellectual Property
Organization
International Bureau



547665

(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/101945 A2

- (51) International Patent Classification⁷: **E21B**
- (21) International Application Number:
PCT/US2004/014519
- (22) International Filing Date: 10 May 2004 (10.05.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/469,700 12 May 2003 (12.05.2003) US
- (71) Applicant and
(72) Inventor: **STONE, Herbert, L.** [US/US]; P.O. Box
22781, Houston, TX 77227-2781 (US).

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,


Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations

[Continued on next page]

- (54) Title: METHOD FOR IMPROVED VERTICAL SWEEP OF OIL RESERVOIRS

HORIZONTAL WELL APPLICATION IN A PATTERN ELEMENT



(57) Abstract: In a WAG flood oil is displaced from a subterranean formation by injecting water alternately with gas into a single injection completion per pattern. The ratio of water to gas injected is the WAG ratio. In this invention, two separate injection completions are used in each pattern, with one placed directly above the other. A very low WAG ratio is used for injection into the bottom extremity of the formation. A very high WAG ratio is injected into the upper interval, at as high a rate can safely be used without fracturing the formation. In the preferred embodiment, two horizontal well bores serve as the two completion intervals. Proper design of this method gives a vertical sweep efficiency of the gas that is several-fold greater than the best of previous WAG flood designs, especially in thin formations.



— of inventorship (Rule 4.17(iv)) for US only

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.